

Skat-Trak Impeller Applications

Revised 7-2011

Kawasaki Watercraft (1977 - 2011)

Model	Year	Orig. Impeller	Pump Dia.	Recommended Skat-Trak Impeller		
				Stock Engine	Limited Engine	Modified Engine
Ultra 300 LX	2011	n/a	160mm	3-Blade 16/21 160-83-20 Swirl	Call for application	Call for application
Ultra 300 X	2011	n/a	160mm	3-Blade 14/19 160-83-20 Swirl	Call for application	Call for application
Ultra 250 X	07-08	n/a	155mm	13/18 155-75-20 Swirl	Call for application	Call for application
Ultra 260 X	09-11	n/a	155mm	14/19 155-75-20 Swirl	Call for application	Call for application
Ultra 260 LX	09-11	n/a	155mm	14/19 155-75-20 Swirl	Call for application	Call for application
Ultra LX	07-11	n/a	155mm	10/16 155-75-20 Swirl	Call for application	Call for application
Ultra 130 Di	01-04	n/a	Tapered	14/19 Ultra Swirl	14/20 Ultra Swirl	14/21, 14/22 or 14/23 Ultra Swirl
Ultra 150	99-05	n/a	Tapered	14/19 Ultra Swirl	14/20 Ultra Swirl	14/21, 14/22 or 14/23 Ultra Swirl
STX 12-F	04-08	n/a	148mm	13/19 Swirl* or 13/19R Swirl**	14/20 Swirl	Call for application
STX 15-F	04-11	n/a	148mm	13/19 Swirl* or 13/19R Swirl**	Call for application	Call for application
STX	09-11	n/a	148mm	13/19 Swirl* or 13/19R Swirl**	Call for application	Call for application
1200 STX-R	02-05	n/a	148mm	14/24 Swirl* or 14/24 R Swirl**	14/24 Swirl *or 14/24 R Swirl **	14/25 Swirl *or 14/25 R Swirl **
1100 STX DI	00-03	n/a	148mm	13/19R Swirl	14/20 Swirl	14/22 Swirl
1100 STX	97-99	8/22	148mm	13/18 Swirl	13/18 to 13/19 Swirl	14/20 to 14/24 Swirl
900 STX	01-06	12/17	148mm	12/17 Swirl	13/18 Swirl	14/19 Swirl
	97-00	10/24	140mm	14/19 Swirl* or 15/20 Slim Line**	14/19 Swirl* or 16/21 Slim Line**	15/20 Swirl* or 17/22 Slim Line**
1100 ZXi	99-03	7/20	148mm	13/18 Swirl	13/18 to 13/19 Swirl	14/20 to 14/24 Swirl
900 ZXi	95-97	14/22	140mm	14/19 Swirl* or 15/20 Slim Line**	14/19 Swirl* or 16/21 Slim Line**	15/20 Swirl* or 17/22 Slim Line**
900 STS	01-02	n/a	140mm	16/21 Slim Line	17/22 Slim Line	17/23 Slim Line
750 ZXi	95-97	14/22	140mm	13/18 Swirl	13/18 to 14/19 Swirl	14/19 to 15/20 Swirl
750 Xi Sport	98-99	13/18	140mm	12/17 Swirl* or 10/18 Standard**	12/17 Swirl* or 11/19 Standard**	13/18 Swirl* or 13/18 Slim Line**
750 Xi	96-97	13/18	140mm	12/17 Swirl* or 10/18 Standard**	12/17 Swirl* or 11/19 Standard**	13/18 Swirl* or 13/18 Slim Line**
	93-95	8/16 5-blade	140mm	10/18 Standard	11/19 Standard	13/18 Swirl* or 13/18 Slim Line**
800 SX-R	03-11	n/a	140mm	13/18 140-75 Swirl	14/19 140-75 Swirl	15/20 140-75 Swirl
750 Sxi Pro	98-02	9/17	140mm	9/17* or 10/18 Standard**	12/17 Swirl* or 10/18 Standard**	13/18 Swirl* or 13/18 Slim Line**
750 SXi	95-96	9/17	140mm	9/17* or 10/18 Standard**	12/17 Swirl* or 10/18 Standard**	13/18 Swirl* or 13/18 Slim Line**
750 SX	92-95	14/19 alum.	140mm	9/17 Standard	9/17* to 10/18 Standard**	13/18 Swirl* or 13/18 Slim Line**
750 SS	96-97	12/17	140mm	9/17 Standard	9/17* to 10/18 Standard**	13/18 Swirl* or 13/18 Slim Line**
	92-95	14/19 alum.	140mm	9/17 Standard	9/17* to 10/18 Standard**	13/18 Swirl* or 13/18 Slim Line**
750 XIR	94	9/17	140mm	9/17 Standard	9/17* to 10/18 Standard**	13/18 Swirl* or 13/18 Slim Line**
750 STX	98	12/17	140mm	10/18 Standard* or 12/17 Swirl**	13/18 Swirl	14/19 Swirl
750 STS	96-97	12/17	140mm	12/17 Swirl* or 10/18 Standard**	12/17 Swirl* or 11/19 Standard**	13/18 Swirl* or 13/18 Slim Line**
	95	13/18	140mm	12/17 Swirl* or 10/18 Standard**	12/17 Swirl* or 11/19 Standard**	13/18 Swirl* or 13/18 Slim Line**
750 ST	95	13/21	140mm	9/17 Standard	9/17* to 10/18 Standard**	13/18 Swirl* or 13/18 Slim Line**
	93-94	10/18 alum. 5-bl.	140mm	9/17 Standard	9/17* to 10/18 Standard**	13/18 Swirl* or 13/18 Slim Line**
650 TS	89-96	16.5 alum.	140mm	9/17 Standard	9/17* to 10/18 Standard**	11/19 Standard
650 SX	86-93	15 alum.	140mm	8/16 Standard	9/17 Standard	10/18* to 11/19 Standard**
650 X-2	86-95	18 alum.	140mm	8/16 Standard	9/17 Standard	10/18* to 11/19 Standard**
650 SC	91-95	16.5 alum.	140mm	9/17 Standard	9/17* to 10/18 Standard**	11/19 Standard
650 JM	91-92	15 alum.	140mm	9/17 Standard	9/17* to 10/18 Standard**	11/19 Standard
550 SX	90-95	17.5 alum.	Tapered	13/16 Standard	13/16 Standard	14/17 Standard
550 JS	82-89	16 alum.	Tapered	13/16 Standard	13/16 Standard	14/17 Standard
440 JS	77-94	15 alum.	121.7mm	13/16 Standard	13/16 Standard	14/17 Standard
300 SX	87-91	15 alum.	121.7mm	13/16 Standard	13/16 Standard	14/17 Standard
300 JS	86-88	15 alum.	121.7mm	13/16 Standard	13/16 Standard	14/17 Standard

* suggested for maximum bottom-to-mid range acceleration gains.

** suggested for maximum top speed gains.

Refer to the USBA rulebook for a more detailed definition of "Stock", "Limited", and "Modified".